

## FWA-1550H-16xN Series, 16 ports CATV EDFA



### 1. Product Description

FWA-1550H series erbium and ytterbium co-doped high-power fiber amplifier is the latest optical transmission system for CATV FTTH. The optical input number: 1 port of CATV or 2 redundant CATV inputs, 16 ports outputs, of which the total output power range of 1550nm is 27 ~ 37dBm. Multiple output power can be matched according to user demand.

This series product adopts JDSU, Lumentum, II-VI etc multimode high power pump laser as pump source and American OFS closed beam splitter as double-cladding synthesizer. Built-in optical power output stabilization circuit and laser thermoelectric cooler temperature stabilization control circuit ensure the best performance of the EDFA and the long-term stable operation of the laser. The microprocessor software monitors the working status of the laser, and the working parameters are displayed on the digital panel (LCD). Once the laser's working parameters deviate from the allowable range set by the software, the micro-processing will automatically turn off the laser power, and the red light flashes to alert.

### 2. Product feature

- ◆ Top quality: Adopt multi-mode high-power pump laser and the power is optimized through software, which makes the system achieving excellent CNR.
- ◆ Reliability: Adopt 19" 2U standard chassis, built-in high performance modular switching power supply, can work in AC165 ~ 265V city network voltage. DC 48V hot-swappable power supply option is available as well. Dual hot and reserved power supply with Chassis automatic heat dissipation control.
- ◆ Intuitive: The built-in microprocessor monitors the working status of the pump laser, and the working parameters are displayed on LCD.
- ◆ Network management Interface: Web transponder is line with the national standard and compatible with the SCTE HMS standard, achieving WEB monitoring function. The red warning symbol is displayed on the web page, which is convenient for troubleshooting.
- ◆ Adjustable output optical power: Advanced design enables a large adjustable range of output power, and power can be lowered by 0 ~ -3dBm.
- ◆ Built-in optical switch option: There are automatic (prefer) or manual (force) switch mode when CATV signal has main path A and redundant path B optical switch input (OPT SWTTCH). Automatic mode uses the main path A by default, it switches to redundant path B if A input power fails.

**3. Technical Parameters**

Items	Unit	Performance Index	
Optical Operating Wavelength	nm	1535~1565	
Input Optical Power Range	dBm	-10~+10	
Noise Ratio	dB	≤5.0 (0 dBm,@1550nm)	
Gain Flatness	dB	< ±0.3	
Optical Power Output Stability	dB	< ±0.5	
Polarization Sensitivity	dB	<0.2	
Polarization Mode Dispersion	Ps	<0.5	
Input End Pump Leakage Power	dB	≤-30	
Output End Pump Leakage Power	dB	≤-30	
Optical Input, Output Return Loss	dB	>45 (APC Stepped Face)	
Pump Operating Number	PCs	2~5	
Rated Output Power	dBm	27~37	
Linker (IN)	-	SC/APC	
Linker (OUT)	-	SC/APC	
Power Supply/Consumption	V/W	AC165~265 or DC-48/20	
Operating/Storage Temperature	°C	-20~65/-30~70	
Operating/Storage Humidity	%	5~90	
Case Size	mm	530×486×88 (2U)	
Network Management Connector	/	RJ45(following national network management standard, supports WEB)	
Optical Switch	Insertion Loss	dB	<1
	Harass	dB	<-60 (isolation between A and B)
	Switch Time	ms	<10
	Switched Power Threshold Range	dBm	-5~10

**4. Product model series**

Model Number	Total Output Power dBm(mW)	Output No.	Each Output Power (dBm)
FWA-1550H-16x14	27dBm(500mW)	16	14
FWA-1550H-32x11		32	11
FWA-1550H-16x15	28dBm(640mW)	16	15
FWA-1550H-32x12		32	12
FWA-1550H-16x16	29dBm(800mW)	16	16
FWA-1550H-32x13		32	13
FWA-1550H-16x17	30dBm(1000mW)	16	17
FWA-1550H-32x14		32	14
FWA-1550H-16x18	31dBm(1300mW)	16	18
FWA-1550H-32x15		32	15
FWA-1550H-16x19	32dBm(1600mW)	16	19
FWA-1550H-32x16		32	16
FWA-1550H-16x20	33dBm(2000mW)	16	20
FWA-1550H-32x17		32	17
FWA-1550H-16x21	34dBm(2500mW)	16	21
FWA-1550H-32x18		32	18
FWA-1550H-16x22	35dBm(3000mW)	16	22
FWA-1550H-32x19		32	19
FWA-1550H-16x23	36dBm(4000mW)	16	23
FWA-1550H-32x20		32	20
FWA-1550H-16x24	37dBm(5000mW)	16	24
FWA-1550H-32x21		32	21

